

THREE PHASE STAR DELTA STARTERS

Induction & Submersible Motors with / without water level controller



FEATURES :

- 3 Phase Digital HEAVY DUTY STAR DELTA Starter
- 3 no of CT provided for accurate current measuring
- High low voltage protection, Overload and Dry run protection
- Cyclic timer, On delay and Off delay timer Adjustable
- Dry run rest time provided, Current based dry run protection
- Auto switch provided, Once power goes and comes motor start automatically, (with bypass option)
- SPP provided to protect from phase failure and reverse phase from input and output both side.
- Auto and bypass switch provided
- 2 separate display for Digital Volt and Amp meter
- Overload and dry current adjustable
- Adjustable high and low voltage limit,
- Protection enable disable option
- Premium 96x96 enclosure for instruments
- 18 gauge high quality metal flame proof enclosure
- Voltage and current calibration facility
- It will automatically set OL & Dry current value
- Factory Reset facility. Fault indication on display
- Motor on indication & R,Y,B phase indication provided.
- Star to Delta inbuilt timer.



Model No.	Descriptions	Input type	Output type	Supply
SD 1212	Triple Display, Suitable upto 7.5 HP	RYB Three Phase	Star Delta (12, 12, 09 AMP Contractor)	415 VAC, 50 Hz (±10%)
SD 1818	Triple Display, Suitable upto 10 HP		Star Delta (18, 18, 18 AMP Contractor)	
SD 2518	Triple Display, Suitable upto 12.5 HP		Star Delta (25, 25, 18 AMP Contractor)	
SD 3225	Triple Display, Suitable upto 15 HP		Star Delta (32, 32, 25 AMP Contractor)	
SD 4040	Triple Display, Suitable upto 20 HP		Star Delta (40, 40, 40 AMP Contractor)	
SD 5040	Triple Display, Suitable upto 25 HP		Star Delta (50, 50, 40 AMP Contractor)	
SD 6550	Triple Display, Suitable upto 35 HP		Star Delta (65, 65, 50 AMP Contractor)	
SD 8065	Triple Display, Suitable upto 50 HP		Star Delta (80, 80, 65 AMP Contractor)	
SD 9580	Triple Display, Suitable upto 60 HP		Star Delta (95, 95, 80 AMP Contractor)	
Also available upto 500 HP				
FEATURES: AMP/Voltage Display or Overload, Voltage, Dryrun, Phase Loss Phase sequence, Protection, Auto manual function.				
APPLICATIONS: Commercials, Aata Chakki, Pulverizer, Induction motor, Compressor, Agriculture.				



Website: www.ktronics.global
Contact No: +91 9043876528
+91 9444962691
Mail: info@ktronics.global